



1285 Walt
Whitman Road
Melville, New
York 11747-3081
(516) 271-6200
FAX No. (516)
271-8259/8260
<http://www.ul.com>



File E123535
Project 93SC14614

Issued: December 16, 1993
Revised: February 25, 2009

REPORT

on

COMPONENT - POWER SUPPLIES,
INFORMATION TECHNOLOGY EQUIPMENT,
INCLUDING ELECTRICAL BUSINESS EQUIPMENT

Vicor Corp.
Andover, MA

Copyright © 1993 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

D E S C R I P T I O N

PRODUCT COVERED:

USR, CNR - Component - Switching Power Supply, Mini MegaPAC Series,
Model Mpa-a-zbbcccccc-dd-xx.

Mp may be replaced by MM, IMM, or IMP

- Item 0. MegaPAC Type
z = 1 for Mini MegaPAC
- Item 1. Number of Outputs
* aa = any number 0 - 20
- Item 2. Number of Modules **and FlexPACs**
bb = any number 0 - 10
- Item 3. Factory assigned Code (Non-safety related)
cccccc = any alphanumeric combination of up to 6 characters or
blanks
- Item 4. MegaPAC configuration Revision (Optional)
dd = any alphanumeric character or blanks (note: dd = G for RoHS
compliant)
- Item 5. MegaPAC description (Optional)
xx = any alphanumeric combination or blanks (note: xx = LL for
Low Leakage)

ELECTRICAL RATING:

Model	V	Input		Output, (dc)	
		A	Hz	V	A
Mini MegaPAC	115-230 or 100-240 Vac 300 Vdc, 6A	25/15	47-500	0-95	200 max

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

The Model Mini MegaPAC is built using up to five Recognized (QQGQ2) dc-dc converter modules **and/or FlexPACs**. It can be configured by selecting the desired output voltages of the modules and paralleling similar outputs to provide the output configurations described in the Rating section of this report. All units share the same front end primary circuitry and fan cooling. Finished power supply assemblies are intended to be factory connected within electronic data processing equipment or information technology equipment. The signal connector J10 and the DC power output terminals are considered to be SELV.

This product was investigated under the Standard for Information Technology Equipment, Including Electrical Business Equipment, UL 60950-1:2003, First Edition; CAN/CSA C22.2 No. 60950-1-03.

Use - For use only in end-use equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Special Considerations - The following items are considerations that were used when evaluating this product.

The component was submitted by the manufacturer for use in a maximum air ambient of 40°C.

Maximum 1000 W continuous output with 38 cfm forced air cooling.

Conditions of Acceptability - When installed in the end-use equipment, consideration shall be given to the following:

* 1. This component has been judged on the basis of the required spacings in the Standard for Safety of Information Technology Equipment, CAN/CSA C22.2 No. 60950-1-03, UL 60950-1. Sub-Clause 2.10, which would cover the component itself, if submitted for Listing.

2. An acceptable enclosure shall be provided in the end-use.

3. The terminals and connectors are suitable for factory wiring only.

4. This power supply was evaluated for connection to a TN power system.

5. This power supply is considered a Class I product. The power supply shall be properly bonded to the main earthing termination in the end-use.

6. Bonding terminals provided on this equipment have not been evaluated as protective earthing terminals.

7. The secondary outputs of this power supply are considered SELV up to 48 V.

8. This power supply has secondary outputs that exceed 240 VA at a potential of 2 V or more.

9. This power supply has been evaluated for use in 40°C ambient.

10. All isolating transformer employ a Class A electrical insulation system.

11. The individual modules which comprise this unit have earth leakage currents which exceed 3.5 mA at high frequency inputs. For end-product units which operate at input frequencies higher than 63 Hz, the end-product must be provided with industrial type sockets or plugs, and the cross-sectional area of the internal protective earthing conductor may not be less than 1.0 square mm, or the end-product must be additionally evaluated with respect to leakage currents, requirements of UL 60950.